

Xprinter® 芯烨

XINYE

Barcode Printer

XP-DT427B

Create For You



Product close up



Streamlined Industrial Design.



USB 2.0 Interface, High Speed Printer.

XP-DT427B is professional thermal direct label printer produced by Xprinter.

High performance and professional printing various type of labels, small and affordable.

Direct thermal label printer your best choice.

Product Features

- High quality double-walled clamshell design
- 203 dpi resolution models
- Head-up sensor
- USB 2.0
- 8MB SDRAM, 4 MB Flash

Application

- Express logistics industry
- Small office or home office mailings
- Shelf labeling
- Healthcare specimen labeling
- File-folder labeling
- Inventory and asset management

High Speed



High Quality



High performance



Direct Thermal Barcode Printer



Windows 7



Windows 8



Windows 10



Printer model	XP-DT427B
Resolution	8 dots/mm(203 DPI)
Printing method	Direct Thermal
Max. print speed	127 mm (5")/s
Max. print width	108 mm (4.25")
Max. print length	1778 mm (70")
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	20-118mm (0.78"-4.6")
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.8 mil)
Label length	10 ~ 2,286 mm (0.4" ~ 90")
Label roll capacity	127 mm (5") OD (outside wound)
Enclosure	Double-walled plastic
Physical dimension	210.8 mm (W) x 190.20 mm (H) x 180.2 mm (D)
Weight	1.40 kg
Processor	32-bit RISC CPU
Memory	4MB Flash Memory
	8MB SDRAM
	SD card reader for Flash memory expansion, up to 4 GB
Interface	USB 2.0
Power	External universal switching power supply
	Input: AC 100-240V, 2.5A, 50-60Hz
	Output: DC 24V, 2.5A, 60W
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: red, purple & blue)
Sensors	Black mark reflective sensor (position adjustable)
	Head open sensor
	Transmissive gap sensor
Internal fonts	8 alpha-numeric bitmap fonts
	Windows fonts are downloadable from software.
Barcode	1D bar code: Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
	2D bar code: CODABLOCK F mode, DataMatrix, Maxicode, PDF-417, Aztec, MicroPDF417, QR code, RSS Barcode (GS1 Databar)
Font and barcode rotation	0°、90°、180°、270°
Printer language	TSPL(EPL、ZPL、DPL)
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing
	Storage: -40 ~ 60°C, 10 ~ 90% non-condensing
Safety regulation	FCC、CE、CCC、CB
Environmental concern	RoHS
Accessories	①Windows labeling software, driver and user manual CD ②quick start guide ③USB cable ④power cord ⑤external switching power adapter ⑥label spindle, fixing tab x 2
Factory options	① Real time clock ② Peel-off module
User options	① external roll mount (1"core) ② external roll mount board ③ Label case



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
[Http://www.poskeytech.com](http://www.poskeytech.com)
 Email: overseas@xprinter.net